

MillerBevco.com

77201-V

High Profile Foot Switch Operated Variable Speed Basic Turntable

OVERVIEW

When you need a way to stretch wrap loads on an infrequent basis, increase worker productivity and minimize worker fatigue consider the 77201-V. With the soft start and stop, loads will not shift or jerk and the speed can be adjusted for lighter loads. Just load the 48" round or octagon turntable, attach the film, set the turntable speed, press the footswitch and wrap the pallet as it turns. The stand alone control panel allows the operator to wrap standing anywhere around the load. The 77201-V is mobile, simple to operate and will eliminate worker fatigue.



SPECIFICATIONS

Maximum Load Size:	56" x 56"
Production Capacity:	20 Loads Per Hour
Machine Dimensions:	48"L x 48"W x 14 5/8"
Weight Capacity:	4,000 lbs.
Electrical Data:	120 VAC 60 Hrtz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" Round Steel Diamond Deck or 48" Octagon Steel Diamond Deck with 5" Safety Skirt
Turntable Height:	14 5/8"
Turntable Drive:	3/4 Hp DC Motor (Totally Enclosed Fan Cooled)
	Variable Speed Turntable 0 to 15 RPM with Soft Start and Soft Stop
	Lubrication Free Enclosed Gear Drive Design
	Synthetic Lube in all Gearboxes (-30 to 120 °F)

Controls:	Pedestal Mounted Stand Alone Control Panel Power On / Off with Indicator Turntable Speed Dial Emergency Stop Button Shielded Footswitch Start / Stop
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Forklift Portable from Front and Rear
Warranty:	3 Year Limited Warranty (100% of All Components)
Shipping Weight:	584 lbs.

Miller/Bevco 6209 Richards Dr. Shawnee, KS 66216 1-800-821-2177

Ph: 913-321-6800 Fax: 913-322-1729 MillerBevco.com

© Copyright 2013 NitechIPM. All Rights Reserved. Specifications, design, accessories or pricing without notice. Artwork does not indicate model or year and may only be reproduced with written permission from NitechIPM