

Bundling Solutions Since 1921

Semi Automatic L-Bar Shrink Wrapper



Features:

- * AlChrome Alloy Sealing Wire
- * Adjustable Discharge Conveyor
- * Magnetic Hold Down Sealing Operation
- * Adjustable Pin Perf Air Evacuation
- * Automatic Cycle Timing
- * Powered Film Feed
- * Adjustable Height Film Inverting Plows
- * Inline Product Feeding

Specifications:

Machine Size:	90"L x 64"W x 53"H
Min/Max Package Size:	L - .5" / 34.5" W - 4" / 26.5" H - .125" / 11"
Sealing Bar:	35.5"L x 27.5"W
Power Requirements:	220V / 1PH / 11A

Shrink Tunnel



Features:

- * PID Temperature Control
- * Teflon Mesh Belt
- * Variable Speed Conveyor
- * Heat Guards for Operator Protection
- * High Efficiency Heating Tubes
- * Heat Recirculating Air System

Specifications:

Machine Size:	72"L x 32"W x 64"H
Package Size:	18"W (max.) 12"H (max.)
Chamber Size:	48"L x 22"W x 15"H
Conveyor Speed:	98 fpm (adjustable)
Power Requirements:	220V, 1/3 PH, 48/28 A