

MODEL 110

Automatic Label APPLICATOR



MODEL 110 Left Hand
Automatic Label Applicator



MODEL 110 Right Hand
Automatic Label Applicator



MODEL 110

Automatic Label Applicator

- Very economical for large production runs.
- 1250" continuous web speed per minute.
- Maintains consistent and high label registration.
- Easily adjustable guides provide versatility of web width, from 1/4" to 4 1/2".
- Solid-state electronics keep production downtime to a minimum.
- Mounts directly onto existing conveyor system.
- Right or left hand models available.

MODEL 110 RH

(right hand)



EQUIPMENT SPECIFICATIONS:

DIMENSIONS: (overall)

Width: 15 in. / 38 cm; Length: 23 in. / 58 cm; Height: 24 in. / 61 cm

WEIGHT: 29 lbs. / 13 kg

ELECTRIC: 115 VAC / 60HZ / 1 AMP (max.)

AIR: n/a PSIG (max.) / n/a CFM

LABEL SPECIFICATIONS:

Standard 4 1/2 in. Web Width / 10" O.D. Roll with 3" Core
Pressure sensitive / Die Cut.

SHIPPING WEIGHT: 35 lbs. / 16kg

SHIPPING CRATE DIMENSIONS: (approx.)

Width: 18 in. / 46 cm; Length: 18 in. / 46 cm; Height: 18 in. / 46 cm

Options Available

- Photoelectric label sensor.
- Photoelectric product sensor.
- Model 810 Adjustable Heavy Duty Stand.
- Model 600 series automatic labeling systems.
- Model 310 Hot Stamp Imprinter.
- Wide label web width kits.
- Spare parts kit.
- Label wipe down: roller, brush, or air assist.

DISTRIBUTED BY:



MillerBevco

UNIQUE PACKAGING SOLUTIONS

6209 Richards Dr.

Shawnee, KS 66216

Tel: 800-821-2177

Info@MillerBevco.com

www.MillerBevco.com



DIVISION OF BICOTH-MANUFACTURING COMPANY

3101 Industrial Avenue Two, Fort Pierce, Florida 34946

Toll Free 800-634-5376 772-465-4441 FAX 772-465-5177