

77203-AW

High Profile Fixed Speed Turntable with Pendant Control & Quick-Load Film Dispenser

OVERVIEW

When it comes to an economical wrapping application the 77203-AW is hard to match. These stretch wrap machines come equipped with a variable speed film carriage to move the Quick-Load film dispenser up and down. Just preset the film carriage's vertical speed on the control board and adjust the manual brake for film tension. Then, load the 48" turntable and attach the film. While the load turns you control the up and down movement of the dispenser and the turntable rotation with the pendant control. Increase productivity, economize film usage, and have tighter load security.



SPECIFICATIONS

Maximum Load Size:	52" x 52" x 76"
Production Capacity:	30 Loads Per Hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	4,000 lbs.
Electrical Data:	120 VAC 60 Hrtz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" Round Steel Diamond Deck with 2" Safety Skirt
Turntable Height:	14 5/8"
Turntable Drive:	3/4 Hp AC Motor (Totally Enclosed Fan Cooled) Fixed Turntable Speed: 0 to 15 RPM (Optional Speeds Available)

SyntHetic Lube in all Gearboxes (-30 to 120 °F)
Pendant Control with: Turntable On / Off Control
Film Carriage Up / Down Controls
Dispenser Speed Board

Lubrication Free Enclosed Gear Drive Design

Film Delivery:	Quick Load Film Dispenser Manually Adjustable Variable Film Stretch (Load Brake) Stretch Level 30% - 150% Force to Load Accepts 12" to 20" Rolls of Stretch Film
Film Carriage:	74" Wrap Height (Optional Wrap Height Available) Top Over Wrap Variable Speed Carriage 0 to 20 RPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Forklift Portable from Front and Rear
Warranty:	3 Year Limited Warranty (100% of all Components)
Shipping Weight:	950 lbs.

Controls: