

## 77205

## High Profile Fixed Speed Turntable with Toggle Switch Operated Variable Speed Quick-Load Film Dispenser

## **OVERVIEW**

When it comes to automating a hand wrapping application the field-tested 77205 is hard to match. These stretch wrap machines come equipped with a variable speed film carriage to move the Quick-Load film dispenser up and down. Just load the 48" round or octagon turn table, attach the film, set the film carriage's vertical speed and the dispenser's stretch wrap tension. While the load turns you can vary the speed as you control the up and down movement of the dispenser with a toggle switch. Increase productivity, economize film usage and have tighter load security.



## **SPECIFICATIONS**

	Maximum Load Size:	52" x 52" x 74" (120" Mast Height Available)
	Production Capacity:	30 Loads Per Hour
	Machine Dimensions:	85"L x 48"W x 83"H
	Weight Capacity:	4,000 lbs.
	Electrical Data:	120 VAC 60 Hrtz 20 Amps Conventional Style 3 Prong Power Cord UL Approved Components.
	Turntable Size:	48" Round Steel Diamond Deck Or 48" Octagon Steel Diamond Deck with 5" Safety Skirt
	Turntable Height:	14 5/8"
	Turntable Drive:	3/4 Hp AC Motor (Totally Enclosed Fan Cooled) Fixed Turntable Speed: 12 RPM (Optional Speeds Available) Lubrication Free Enclosed Gear Drive Design Synthetic Lube in all Gearboxes (-30 to 120 °F)
	Controls:	Power On / Off with Indicator

**Dispenser Speed Dial** 

2 Diagnostic Lights Emergency Stop Button

Film Carriage Up / Down Controls

Film Delivery:	Quick Load Film Dispenser Manual Adjusted Variable Film Stretch (Load Brake) Stretch Level 30% - 150% Force to Load Accepts 12" - 20" Rolls of Stretch Film
Film Carriage:	74" Wrap Height (Optional Wrap Heigh Available) Top Over Wrap Variable Speed Carriage 0-20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Forklift Portable from Front and Rear
Warranty:	3 Year Limited Warranty (100% of All Components)
Shipping Weight:	950 lbs.