

Automatic Strapping Machine with Stainless Steel Body

The SQ-800SUS boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection, in an attractive and practical stainless steel body.

■ Stainless Steel Body

The machine is designed for meat/poultry packing or pharmaceutical/lean room applications, where there is exposure to moisture and/or keeping hygiene is important. The fully enclosed stainless steel cabinet protects the components from moisture exposure. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest.

■ Strapping Speed

Standard strapping rate is 54 straps/min, even when a tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ Less Dusting and Less Moving Parts, with Self-Lubricating Design

The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, makes the maintenance easier, and increases operational life of the machine.



SQ-800SUS

Standard Specifications (Arch size 650 mm wide x 500 mm high or 25" wide x 20" high)

Dimension	Width	1254 mm	49-3/8 in.
	Height	1403 mm	55-1/4 in.
	Depth	609 mm	24 in.
	Weight	126 kg	277 lbs.
Table Height		795 mm	31-1/4 in.
Package Size	Max	W 620 X H 480 mm	W 24-1/2 X H 18-7/8 in.
	Min	W 80 X H 30 mm	W 3-1/8 X H 1-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		784 N (80 kgf)	176 lbf
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2018 Strapack Corporation

DISTRIBUTED BY:

 **MillerBevco**
UNIQUE PACKAGING SOLUTIONS
6209 Richards Drive
Shawnee, Kansas 66216
Tel: 800-821-2177/ Fax: 913-322-1729
Info@MillerBevco.com
www.MillerBevco.com



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone 1-510-475-6000 Fax. 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521