



77204D-LP Low Profile Semi-Automatic Stretch Wrapper with Brake-Motor Powered Stretch Film Delivery

If you are looking for a medium-duty, low maintenance stretch wrapper the 77204D-LP is the answer. With this easy to operate machine you load the 48" variable speed turntable, attach the film to the load, select from 5 modifiable programs, press the start button and walk away. The carriage travels up wrapping the load until the photo eye senses the top of the load. When the top of the load is sensed a preset number of wraps are applied. When the number of top wraps is completed the film carriage then reverses direction and continues to wrap the load as it lowers. After the bottom of the load is reached the turntable stops in the same position that it started for easy unloading. The 77204D-LP offers the best value and features for a semi-automatic stretch wrapper found on today's market.

SPECIFICATIONS

Maximum Load Size:	52" x 52" x 80" (120" Mast Height Available)
Production Capacity:	30 Loads Per Hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	4,000 lbs.
Electrical Data:	120 VAC 60 Hertz 20 Amps. Conventional Style 3 Prong Power Cord UL Approved Components
Turntable Size:	48" Round Steel Deck with 2" Safety Skirt
Turntable Height:	2 7/8"
Turntable Drive:	3/4 Hp DC Motor (Totally Enclosed Fan Cooled) Variable Speed Turntable 0 to 15 RPM with Soft Start and Soft Stop 4 Point Cam Follower Turntable Supports Easy Access Lubrication Points on Turntable Heavy-Duty #50 Roller Chain And Drive Sprocket Synthetic Lube in all Gearboxes (-30 to 120°f) Turntable Indexing Home Alignment
Controls:	PLC-Programmable Logic Control with Pre-Programmed Sequences Turntable Variable Speed Dial Dispenser Variable Speed Dial Film Tension Variable Dial Emergency Stop Button Photo Eye for Automatic Load Height Sensing On/Pause Button Start/Resume Switch 3 Indicator Light, Power, Ready, and Tension Liquid CryStal Display



Ramp and scale option available

★ MADE IN THE USA ★



Film Delivery:	Brake Motor Powered Stretch 8 Setting Adjustable Variable Film Stretch (Brake Roller) Stretch Level 30% to 150% Force to Load Accepts 12" to 20" Rolls of Film on Standard 3" Core
Film Carriage:	Film Carriage Top Delay and Auto-Stop Heavy Duty Enclosed Gear Drive Variable Speed Carriage 0 to 20 FPM 1/4 Hp 90 Volt DC Motor Dispenser Kill Switch Top / Bottom
Tower Construction:	Formed All Steel Tower 80" Wrap Height (Optional Wrap Height Available) #40 Chain Drive Lift UHMW Full Tower Slides
Frame Construction:	Custom Formed 3/8" Steel Channel All Welded Steel Construction Easy Access to all Components Forklift Portable from Front or Rear
Warranty:	3 year limited warranty (100% of all components)
Shipping Weight:	1,125 lbs.