



Innovative semi automatic palletizer
Handy and economical way
to secure your pallets!



■ Versatile Tension Capability

Manual tension or automatic tension is available by means of a simple selector switch

<Manual Tension Mode>

The strap tension can be controlled manually via the operation bar, allowing edge protection to be secured to the pallet prior to strap completion

<Automatic Tension Mode>

Strap tension is applied automatically at a preselected level.

■ Simple Operation

It is simple to use. The use of the operation bar (manual tension) and the start switch are only needed for complete strap operation.

■ 4-Way Pallet Entry

The bayonet height can be adjusted to 3/5" and 1" by a simple lever. It allows cross strapping through various sized pallet openings



■ Lower Sealing for Smaller Pallets

Sealing point is only 12 7/8" from the floor. Smaller pallet can now be easily strapped.

SPECIFICATIONS

Width	2210mm	87"
Height	1012mm	39 4/5"
Depth	756mm	29 4/5"
Machine Weight	approx 100kg	220 lbs
Bayonet Height	15, 25mm	3/5", 1"
Package Size	min. 380mm / 15" (Height)	

Strap Width	6, 9, 12, 15.5mm
	1/4", 3/8", 1/2", 5/8"
Strap tension	9-690N (9-70kgf)
	(20-156 lbs)
Sealing Method	heat seal
Power Supply	100, 110, 120, 200, 220, 230, 240v
	Single Phase 50/60Hz 0.4kw

DISTRIBUTED BY

Miller/Bevco since 1965 www.MillerBevco.com Info@MillerBevco.com	6209 Richards Dr. Shawnee, KS 66216 Ph: 800-821-2177/913-322-6800 Fax: 913-322-1729
---	--

Strapack Corporation

1-2-17 Higashi Shimbashi, Minato-ku Tokyo 105-0021 Japan
phone 81-3-3289-1161 fax 81-3-3289-1160
(URL) <http://www.strapack.com> (E-mail) info@strapack.com

Strapack Inc

30860 San Clemente St., Hayward, CA 94544 U.S.A.
Phone (510) 475-6000 Fax (510) 475-6009