

## Automatic Side-Seal Strapping Machine

The SQ-800Y with brushless DC Motor is a side-seal model which boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection.

### ■ Wide Adaptability

#### to Fully-Automated Packaging Line

The machine fits any existing or proposed conveyor system, adapts to any conveyor height and requires no special equipment.

Several options are available to make it easy to integrate the SQ-800Y into a conveyor system. Larger arch sizes offer a wide range of applications, particularly for large and heavy packages.

### ■ Strapping Speed

Standard strapping rate is 50 straps/min, even when tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.



## SQ-800Y

### Standard Specifications (Arch size 600 mm wide x 850 mm high or 23" wide x 33" high)

Dimension	Width	1500 mm	59-1/8 in.
	Height	1723 mm	67-3/4 in.
	Depth	610 mm	24 in.
	Weight	180 kg	397 lbs.
Package Size	Max	W 580 X H 820 mm	W 22-7/8 X H 32-1/4 in.
	Min	W 30 X H 80 mm	W 1-1/4 X H 3-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		784 N (80 kgf) 150mm stroke	176 lbf 6 in. stroke
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.  
Modification rights reserved.

© 2020 Strapack Corporation

### DISTRIBUTED BY:



**MillerBevco**  
UNIQUE PACKAGING SOLUTIONS

Tel: 800-821-2177/Fax: 913-322-1729

Info@MillerBevco.com

www.MillerBevco.com



ISO 9001 and 14001 Certified

### STRAPACK CORPORATION

8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN

Phone 81-3-6278-1806 Fax. 81-3-6278-1807

(URL) <http://www.strapack.com> (E-mail) [info@strapack.com](mailto:info@strapack.com)

### STRAPACK INC.

33508 Central Avenue, Union City, CA 94587-2097 U.S.A.

Phone 1-510-475-6000 Fax. 1-510-475-6090

### STRAPACK, N.V./S.A.

Uilenbaan 200, B-2160 Wommelgem, BELGIUM

Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521