

Compact Automatic Strapping Machine

The SQ-800IR boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection, in an attractive and compact body.

■ Compact Body

Space-efficient design with internal reel unit utilizing a standard size strap coil. This compact body is ideal for office or printing applications.

■ Strapping Speed

Standard strapping rate is 54 straps/min, even when tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ Less Dusting and Less Moving Parts, with Self-Lubricating Design

The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, allows for easier maintenance, and increases operational life of the machine.

■ Arch Configuration

Arch configuration accommodates U.S. Mail trays with 690mm (27") opening.



SQ-800IR

Standard Specifications (Arch size 690 mm wide x 400 mm high or 27" wide x 16" high)

Dimension	Width	916 mm	36 in.
	Height	1394 mm	54-7/8 in.
	Depth	609 mm	24 in.
	Weight	151 kg	277 lbs.
Table Height		885 mm	34-7/8 in.
Package Size	Max	W 620 X H380 mm	W 24-1/2 X H 15 in.
	Min	W 80 X H 30 mm	W 3-1/8 X H 1-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		784 N (80 kgf)	176 lbf
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2019 Strapack Corporation

DISTRIBUTED BY:



MillerBevco
UNIQUE PACKAGING SOLUTIONS

6209 Richards Drive
Shawnee, Kansas 66216
Tel: 800-821-2177/Fax: 913-322-1729
Info@MillerBevco.com
www.MillerBevco.com



ISO 9001 and 14001 Certified

STRAPACK CORPORATION

8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone 1-510-475-6000 Fax. 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521